

## PRODUCTO

### BISAGRA OCULTA MODELO 505, ZAMAK Y ACETAL

#### ► DESCRIPCIÓN

Bisagra invisible, modelo 505, para puertas de paso no solapadas y para marcos de madera. Profundidad de fresado reducida de 21 mm. Sistema funcional de bisagra completamente oculto. Regulación en 3 sentidos (lateral +/- 1,5 mm, altura +/- 2,5 mm, profundidad +/- 1,0 mm). Hasta 40 kg, (2 bisagras). Medidas: 110 x 24 mm. Material: Zamak y acetal.




#### ► MATERIAL

Zamak.

#### ► ACABADO

Cromo satinado, níquel satinado, negro satinado y blanco.

## IMÁGENES



## OTROS DATOS

### REF. AN 140 3D

**MEDIDA:** 110x24 mm

#### CÓDIGO

#### REFERENCIA

#### ACABADO

96309

AN 140 3D-14

Cromo satinado

96310

AN 140 3D-44

Níquel satinado

96311

AN 140 3D-18

Negro satinado

96312

AN 140 3D-49

Blanco

## AN 140 3D

for unrebated residential doors up to 40 kg

hinge		up to 40 kg
-------	--	-------------

### Product features

- completely concealed hinge system
- for timber frames
- for unrebated residential doors
- 3D adjustable (side +/- 1.5 mm, height +/- 2.5 mm, compression +/- 1.0 mm)
- material zamak / acetal

### Technical details

load capacity	<b>i</b> 2 hinges per door leaf (900x2100 mm)	40.0 kg
overall length		110.0 mm
width (frame)		24.0 mm
width (door)		24.0 mm
cutter diameter		14.0 or 16.0 mm
collar ring diameter		25.0 or 27.0 mm
opening angle		180°

### Finish

Satin Chrome (AN 014), Coated Bronze (AN 017), Black (AN 018), Antique Bronze (AN 035), Aluminium Chrome (AN 036), Polished Brass (AN 037), Polished Chrome (AN 039), Satin Nickel (AN 044), RAL 9016 Traffic White (AN 049)

### Combination

receiver	casing frame	AN 140 3D FZ
----------	--------------	--------------

### Note

**i** The load capacity mentioned above refers to the use of 2 hinges per door leaf (900 x 2100 mm).

Suggested screws:

Frame side: Countersunk head screws DIN 7505 A, Diameter 4.5 mm

Door side: Pan head screws DIN 7505 B, Diameter 4.5 mm